



表 2 钢板标称厚度

单位为毫米

防盗安全级别	1 级	2 级	3 级	4 级	5 级
门扇防护面板、 非防护面板	≥0.8	防护面板≥1.0 非防护面板≥0.8	≥1.0	≥1.0	≥3.0
门框	≥1.5	≥1.8	≥2.0	≥2.0	≥3.0
下框(不锈钢材质)	≥0.8	≥1.0	≥1.2	≥1.2	≥2.0

表 3 钢板厚度允许负偏差

单位为毫米

标称厚度	3.00	2.00	1.80	1.50	1.20	1.00	0.80
允许负偏差	-0.22	-0.12	-0.12	-0.09	-0.07	-0.06	-0.05

表 4 门框、门扇对角线尺寸公差及门框槽口、门扇的高度与宽度公差


单位为毫米

尺寸	<1 000	1 000~<2 000	2 000~3 500	>3 500
公差	≤2.0	≤3.0	≤4.0	≤5.0

— — —
— — —
—

— — — — —





	<div style="text-align: center;"> <hr style="width: 50%; margin: 0 auto;"/> <hr style="width: 30%; margin: 0 auto;"/> <hr style="width: 50%; margin: 0 auto;"/> <hr style="width: 50%; margin: 0 auto;"/> <hr style="width: 50%; margin: 0 auto;"/> </div>									
